ULTRA-LOW EMISSIONS

NEAR ZERO (CO)

Produces up to 1 parts per million of carbon monoxide. OSHA Standard allows up to 50.



PORTABLE HEAT

Includes rubber no-flat wheels, a foldable handle, and two heavy-duty fixed handles on the fuel tank.

EZ-LIFT CRANE BRACKET Sold as an accessory.



BUILT FOR DURABILITY







SPECIFICATIONS

BTU/Hour:	High: 147,000 (43kW) Low: 130,000 (38kW)
Fuel:	Type: Diesel or No. 2 fuel Tank Capacity: 19 Gallons
Run Time:	High: 17 Hours Low: 19 Hours
Flow Rate:	High: 1.10 GPH Low: .97 GPH

Electrical Requirements:

120V 2A 60HZ or 12V Pure Sine Power Inverter (800W Minimum)

Overall Dimensions:

29"W x 35"L x 41"H (73.7cm x 88.9cm x 104.1cm)

Weight:

Empty Tank: 195 pounds (88kg) Full Tank: 320 punds (145kg)

Minimum Clearance (Combustible Items)

Front: 72"Right Side: 36"Back N/ALeft Side: 36"

* Use in well ventilated areas. Not for indoor residential use.



SunFireHeater.com



THE ULTIMATE HEATER LOW NOISE & ODORLESS RADIANT HEAT



SUNFIRE 150

(h) 150,000 BTU

DIESEL-FIRED

BETTER PERFORMANCE

OUTPERFORMS TORPEDO-STYLE **HEATERS**

HEATS LIKE THE SUN Warms objects directly within the radiant wave range without blowing air. **RADIANT WAVE RANGE** 2 ft 9ft 103 °F - 159 °F 6 ft 160 °F - 248 °F 3 ft









TORPEDO-STYLE

THE PROBLEM

- × EXTREMELY LOUD
- × STRONG ODOR
- **X** SHORTER RUN TIMES
- **X** HEATS AIR, NOT OBJECTS

SUNFIRE RADIANT

THE SOLUTION

- **✓** LOW NOISE
- **✓ VIRTUALLY ODORLESS**
- LONG RUN TIMES
- **✓** HEATS OBJECTS DIRECTLY



* Savings may vary depending on current fuel cost.



